


VK NUR














LED COB Adjustable Spotlight On Track

- Material: Aluminium
- Input voltage 220V-240V
- LED 5 years warranty
- Optional special optical lens



LED COB Adjustable Spotlight On Track

- Material: Aluminium
- Input voltage 220V-240V
- LED 5 years warranty
- Optional special optical lens



TECHNICAL DETAILS

Power	Beam	CCT	Flux	CRI	Color	Drive
20W	12D	3000K	1500 lm	RA>80	BK/WH	500mA
	24D	3000K	1460 lm	RA>80	BK/WH	500mA
	36D	3000K	1420 lm	RA>80	BK/WH	500mA
25W	12D	3000K	2075 lm	RA>80	BK/WH	600mA
	24D	3000K	2025 lm	RA>80	BK/WH	600mA
	36D	3000K	1975 lm	RA>80	BK/WH	600mA

- Adjustable angle -side 90
- Rotational angle 350
- Minimum distance 0.2m
- Indoor use
- IP20 Protection degree
- Flammable object surface using
- Surge proof

TECHNICAL DETAILS

Power	Beam	CCT	Flux	CRI	Color	Drive
35W	12D	3000K	2835 lm	RA>80	BK/WH	900mA
	24D	3000K	2800 lm	RA>80	BK/WH	900mA
	36D	3000K	2730 lm	RA>80	BK/WH	900mA
40W	12D	3000K	3160 lm	RA>80	BK/WH	1050mA
	24D	3000K	3120 lm	RA>80	BK/WH	1050mA
	36D	3000K	3080 lm	RA>80	BK/WH	1050mA

- Adjustable angle -side 90
- Rotational angle 350
- Minimum distance 0.2m
- Indoor use
- IP20 Protection degree
- Flammable object surface using
- Surge proof